ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

CERTIFICATE

No. Z2 021860 0185 Rev. 00

Holder of Certificate: **Ledon A/S**
Vestergade 25
Gram
6510 Gram
DENMARK

Certification Mark:

Product: **Swings**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 713153371-1

Valid until: 2024-02-12

Date, 2019-02-21

(Michael Weber)

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

A4 / 07.17

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT
TÜV SÜD

Product Service

CERTIFICATE

No. Z2 021860 0185 Rev. 00

Model(s):

1149, 1160, 1162, 1163, 1169, 1170, 1171, 1171EX, 1171LC, 1171XX, 1171EXA 1172, 1172EX, 1172LC, 1172XX, 1172EXA, 1174, 1175, 1175EX, 1175LC, 1175XX, 1175EXA, 1179, 1180, 1181, 1181EX, 1181LC, 1181XX, 1181EXA, 1182, 1182EX, 1182LC, 1182XX, 1182EXA, 1184, 1185, 1185EX, 1185LC, 1185XX, 1185EXA, 1186, 1186EX, 1186LC, 1186XX, 1186EXA, 1187, 1187EX, 1187LC, 1187XX, 1187EXA, 1188, 1188EX, 1188LC, 1188XX, 1188EXA, 1189, 1189EX, 1189LC, 1189XX, 1189EXA, 1190, 1190EX, 1190LC, 1190XX, 1190EXA, 302230

Parameters:

Swing frames made of galvanised steel pipes Ø 76.1 x 2.9 mm or cedarwood 90 x 90 mm.
Frames could be combined with the following swing seat models: 1110, 1112, 1113, 1114, 1035, 1036.
Model suffixes EX, LC, XX and EXA are only decorational elemen

Model: dimensions (L x W x H); fall height; Possible swing seats

1149: 1.63 x 0.34 x 1.88 m; 1.23 m; 1113
1160: 3.70 x 2.70 x 2.20 m; 1.50 m; 1110, 1112, 1113, 1114
1162: 3.70 x 2.70 x 2.20 m; 1.50 m; 1110, 1112, 1113, 1114
1163: 3.70 x 2.70 x 2.20 m; 1.50 m; 1110, 1112, 1113, 1114
1169: 2.40 x 2.70 x 2.20 m; 1.50 m; 1110, 1112, 1113, 1114
1170: 3.50 x 2.70 x 2.20 m; 1.50 m; 1110, 1112, 1113, 1114
1171: 2.40 x 2.70 x 2.20 m; 1.50 m; 1110, 1112, 1113, 1114
1172: 3.50 x 2.70 x 2.20 m; 1.50 m; 1110, 1112, 1113, 1114
1174: 3.50 x 2.70 x 2.20 m; 1.50 m; 1035, 1036
1175: 3.50 x 2.70 x 2.20 m; 1.50 m; 1035, 1036
1179: 3.85 x 2.90 x 2.50 m; 1.65 m; 1110, 1112, 1113, 1114
1180: 3.85 x 2.90 x 2.50 m; 1.65 m; 1110, 1112, 1113, 1114
1181: 3.85 x 2.90 x 2.50 m; 1.65 m; 1110, 1112, 1113, 1114
1182: 3.85 x 2.90 x 2.50 m; 1.65 m; 1110, 1112, 1113, 1114
1184: 6.53 x 6.22 x 2.40 m; 1.30 m; 1112, 1113
1185: 6.60 x 2.30 x 2.20 m; 1.15 m; 1110, 1112, 1113, 1114
1186: 6.50 x 2.30 x 2.20 m; 1.30 m; 1110, 1112, 1113, 1114, 1035, 1036
1187: 5.30 x 2.30 x 2.20 m; 1.28 m; 1110, 1112, 1113, 1114
1188: 9.70 x 2.30 x 2.20 m; 1.28 m; 1110, 1112, 1113, 1114
1189: 6.35 x 2.30 x 2.20 m; 1.30 m; 1035, 1036
1190: 8.30 x 2.30 x 2.20 m; 1.30 m; 1110, 1112, 1113, 1114, 1035, 1036
302230: 3.50 x 2.70 x 2.20 m; 1.50 m; 1110

Tested according to:

EN 1176-1:2017
EN 1176-2:2017

Production Facility(ies):

021860

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®