



Product Service

CERTIFICATE

No. Z2 021860 0208 Rev. 00

Holder of Certificate: **Ledon A/S**

Vestergade 25
Gram
6510 Gram
DENMARK

Certification Mark:



Product: **Swings**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713330926-01

Valid until: 2029-03-07

Date, 2024-04-09

(Tobias Hofmann)

CERTIFICATE

No. Z2 021860 0208 Rev. 00

Model(s):

1149, 1169, 1169EXA, 1170, 1170EXA, 1171,
 1171EXA 1172, 1172EXA, 1174, 1174EXA, 1175,
 1175EXA, 1176, 1179, 1179EXA, 1180, 1180EXA,
 1181, 1181EXA, 1182, 1182EXA, 1185, 1185-0,
 1185EXA, 1185EXA-0, 1186, 1186-0, 1186EXA,
 1186EXA-0, 1187, 1187-0, 1187EXA, 1187EXA-0,
 1188, 1188-0, 1188EXA, 1188EXA-0, 1189, 1189-0,
 1189EXA, 1189EXA-0, 1190, 1190-0, 1190EXA,
 1190EXA-0, 302230, LB1177, LB1178

Parameters:

Swing frames made of galvanised steel pipes Ø 76.1 x 2.9 mm.
 Frames could be combined with the following swing seat models:
 1110, 1112, 1114, 1115, 1035, 1036.
 Model suffixes EXA, LB are decorative elements.

Model: dimensions (L x W x H); Possible swing seats

1149: 1.63 x 0.34 x 1.88 m; 1113
 1169: 2.40 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114
 1169EXA: 2.40 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114
 1170: 3.50 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114
 1170EXA: 3.34 x 2.27 x 2.43 m
 1171: 2.40 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114
 1171EXA: 2.23 x 2.27 x 2.43 m; 1110
 1172: 3.50 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114
 1172EXA: 3.34 x 2.27 x 2.43 m; 1110
 1174: 3.50 x 2.70 x 2.20 m; 1035, 1036
 1174EXA: 3.34 x 2.27 x 2.43 m
 1175: 3.50 x 2.70 x 2.20 m; 1035, 1036
 1175EXA: 3.34 x 2.27 x 2.43 m, 1036
 1176: 3.50 x 2.70 x 2.20 m; 1036
 1179: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114
 1179EXA: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114
 1180: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114
 1180EXA: 3.46 x 2.61 x 2.79 m; 1110
 1181: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114
 1181EXA: 2.36 x 2.61 x 2.79 m; 1110
 1182: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114
 1182EXA: 3.46 x 2.61 x 2.79 m; 1110
 1185: 6.60 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114
 1185-0: 6.60 x 2.30 x 2.20 m
 1185EXA: 6.35 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114
 1185EXA-0: 6.35 x 2.27 x 2.43 m
 1186: 6.50 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114, 1035, 1036
 1186-0: 6.50 x 2.30 x 2.20 m
 1186EXA: 6.25 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114, 1036
 1186EXA-0: 6.25 x 2.27 x 2.43 m
 1187: 5.30 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114
 1187-0: 5.30 x 2.30 x 2.20 m
 1187EXA: 5.05 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114
 1187EXA-0: 5.05 x 2.27 x 2.43 m
 1188: 9.70 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114

CERTIFICATE

No. Z2 021860 0208 Rev. 00

1188-0: 9.70 x 2.30 x 2.20 m
1188EXA: 9.37 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114
1188EXA-0: 9.37 x 2.27 x 2.43 m
1189: 6.35 x 2.30 x 2.20 m; 1035, 1036
1189-0: 6.35 x 2.30 x 2.20 m
1189EXA: 6.14 x 2.27 x 2.43 m; 1035, 1036
1189EXA-0: 6.14 x 2.27 x 2.43 m
1190: 8.30 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114, 1035, 1036
1190-0: 8.30 x 2.30 x 2.20 m
1190EXA: 7.96 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114, 1035, 1036
1190EXA-0: 7.96 x 2.27 x 2.43 m
302230: 3.50 x 2.70 x 2.20 m; 1110
LB1177: 2.40 x 2.70 x 2.20 m; 1115
LB1178: 3.50 x 2.70 x 2.20 m; 1115

**Tested
according to:**

EN 1176-1:2017
EN 1176-2:2017